

IV Year - I Semester

L	T	P	C
0	0	3	2

MICROWAVE ENGINEERING & OPTICAL LAB

Minimum Twelve Experiments to be conducted:

Part – A (Any 7 Experiments (8 & 9 compulsory)) :

1. Reflex Klystron Characteristics.
2. Gunn Diode Characteristics.
3. Attenuation Measurement.
4. Directional Coupler Characteristics.
5. Impedance and Frequency Measurement.
6. Scattering parameters of Circulator.
7. Scattering parameters of Magic Tee.
8. Radiation Pattern of Horn and Parabolic Antennas.
9. Synthesis of Microstrip antennas (Rectangular Structure) Using HFSS.

Part – B (Any 5 Experiments) :

10. Characterization of LED.
11. Characterization of Laser Diode.
12. Intensity modulation of Laser output through an optical fiber.
13. Measurement of Data rate for Digital Optical link.
14. Measurement of NA.
15. Measurement of losses for Analog Optical link.

Equipment required for Laboratories:

1. Regulated Klystron Power Supply, Klystron mount
2. VSWR Meter
3. Micro Ammeter
4. Multi meter
5. CRO
6. GUNN Power Supply, Pin Modulator
7. Crystal Diode detector
8. Micro wave components (Attenuation)
9. Frequency Meter
10. Slotted line carriage
11. Probe detector
12. Wave guide shorts
13. SS Tuner
14. Directional Coupler
15. E, H, Magic Tees
16. Circulators, Isolator
17. Matched Loads
18. Pyramidal Horn and Parabolic Antennas
19. Turntable for Antenna Measurements
20. HFSS Software
21. Fiber Optic Analog Trainer based LED
22. Fiber Optic Analog Trainer based laser
23. Fiber Optic Digital Trainer
24. Fiber cables - (Plastic, Glass)